

# DAMARK

## SHRINK PACKAGING SYSTEMS

# STANDARD SHRINK TUNNELS

The ST Series:  
For Use With L Bar Sealers

We offer all of our shrink tunnels with either roller conveyors (R) or belt conveyors (B). The letter after ST in the model name dictates the style. The number in the model name refers to the tunnel's width.

STR-16  
pictured



## Low Production Tunnels

### Standard Features

Console units with heavy gauge steel body and welded tubular steel frame and base.

Chamber temperature is thermostatically controlled through an electronic time proportional temperature controller guaranteeing maximum temperature variation in the shrink chamber of no more than 2 degrees Fahrenheit.

Variable speed live or dead roller conveyor system with silicone covered, solid steel rollers set on 2" centers. A belt type conveyor is available as an option.

Heavy-duty casters.

Automatic shutdown cycle.

Available Models: **STR/B-16** | **STR/B-16D**

STR-24  
pictured



## Medium Production Tunnels

### Standard Features

All the features listed above, with the following upgrades;

Specially designed two speed Turbo blower driven by a 1/8 HP twin speed blower motor.

A bottom shrink section that ensures perfect all around shrink.

Tunnel height can be increased in 4" increments.

Available Models: **STR/B-16A** | **STR/B-24** | **STR/B-34**

STR-16AD  
pictured



## High Production Tunnels

### Standard Features

Multiple zone tunnels, with the features listed above, are available for high speed applications.

Available Models: **STR/B-16AD** | **STR/B-16ADD**

AutoCAD or JPEG layout drawings and CD videos are available upon request.

# DAMARK

## SHRINK PACKAGING SYSTEMS

# HEAVY DUTY SHRINK TUNNELS

## The S Series:

For Use With Sleeve Wrappers And In Certain L Bar Sealer Applications

Generally used for shrinking polyethelene shrink film, the Damark line of heavy duty shrink tunnels can be built to suit your specific needs. The tunnel openings are available in 10" increments in width starting at 24" wide and have a maximum height of 54".

S44T  
pictured



## S Series Shrink Tunnel

### Standard Features

- All welded tubular steel construction with heavy duty casters.
- High insulation factor for maximum efficiency.
- Solid state temperature control assures consistent heating.
- Custom, high efficiency turbo blowers move more than twice the air at half the speed of conventional designs.
- Heavy duty 1/2 HP blower motors.
- High quality conveyor drives with solid state speed controls.
- Easy access control panels simplify maintenance.
- Multiple zone tunnel configurations to meet production speed requirements.
- Optional pack coolers for high speed applications.

Available Models: **S24 | S24T | S24T-3 | S34 | S34T | S34T-3 | S44T | S44T-3 | S54T-4 | S64T-4**

## Unique Shrink Tunnel Applications

Below are examples of two custom built tunnels.



**S54**  
Non standard size



**S34-T**  
Non standard color

### DAMARK PACKAGING INC.

phone: 416-609-8011  
toll free: 800-265-1775  
fax: 416-298-4328  
info@damarkpackaging.com  
www.damarkpackaging.com

**PLEXPACK**



### DISTRIBUTED BY

**West Coast Plastics Equipment, Inc.**  
800-392-8569  
www.sealer.net